



Shell Helix *Ultra Maserati* 5W-40

Passenger Car Motor Oil

Shell Helix Ultra Maserati 5W-40 uses unique active cleansing technology to help high-performance engines operate at maximum efficiency by helping to protect them from power-robbing deposits and wear. It is designed to meet the demanding requirements of Maserati high-performance engines.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

▪ Shell's ultimate active cleansing technology

Helps to protect high-performance engines from power- and performance-robbing deposits.

Main Applications

Shell Helix Ultra Maserati 5W-40 fully synthetic formulation offers Shell's maximum protection in very hot and extremely cold climates, and severe driving conditions.

Helix Ultra Maserati 5W-40 can be used in modern Maserati gasoline and diesel engines, and it is also suitable for use with biodiesel and gasoline/ethanol blends.

Specifications, Approvals & Recommendations

▪ API SN

▪ ACEA C3

▪ Fiat 9.55535-GH2 - Meets the requirements

▪ For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk

Typical Physical Characteristics

Properties			Method	Shell Helix Ultra Maserati 5W-40
Kinematic Viscosity	@100°C	cSt	ASTM D445	12.78
Kinematic Viscosity	@40°C	cSt	ASTM D445	72.18
Viscosity Index			ASTM D2270	179
MRV	@-35°C	cP	ASTM D4684	14 300
Density	@15°C	kg/m ³	ASTM D4052	835.7
Flash Point		°C	ASTM D92	242
Pour Point		°C	ASTM D97	-45

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

▪ Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

▪ Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.